



Power **52 W**
Luminous flux* **8900 lm (120°)**
Light colour **Neutral white**
IK **09**

Voltage **230 V**
Colour temperature **4000 K**
Beam angle **60 °**
Protection class **IP65**

Technical data:

Product code	SLI028026NW_60_BLACK
Power	52 W
Nominal current	235 mA
Voltage	230 V
Energy efficiency classe	C
Energy consumption	52 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power supply included	+
Power factor	0.92
Useful luminous flux*	8900 lm (120°)
Luminous flux**	8000 lm (360°)
Light efficiency	171 lm/W
Luminous intensity	2500 cd
Colour temperature	4000 K
Light colour	Neutral white
Beam angle	60 °
RA	80
Uniformity of color SDCM max	3
Dimmable	-
Working temperature range	-20/+40 °
Lifespan	50000 h
Housing material	POLYCARBONATE
IK	09
Protection class	IP65
Colour	Czarny/White
Dimension (axbxc)	1490x72x70 mm
For use	Inside/Outside
Assembly method	On the ceiling/Suspended
Application	INT/EXT
Made in	PRC
Other	MAX 16 pcs per line ,



*Applies to the LED source used. **Luminaire luminous flux