

CCT IP54 130
lm/W




CE

Power	5 W	Voltage	230 V
Luminous flux*	650 lm (360°)	Colour temperature	3000/4000/6000 K
Light colour	CCT	Beam angle	180 °
Protection class	IP54		



See more on dedicated page 



 User manual



 Declaration of Conformity



 Photometric file

Technical data:

Product code	SLI003036CCT_PW
Power	5 W
Nominal current	35 mA
Voltage	230 V
Energy consumption	5 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power factor	0.5
Useful luminous flux*	650 lm (360°)
Luminous flux**	400 lm (360°)
Light efficiency	130 lm/W
Colour temperature	3000/4000/6000 K
Light colour	CCT
Beam angle	180 °
RA	80
Light source included	+
Dimmable	No
Working temperature range	-20/+40 °
Lifespan	17000 h
Housing material	PLASTIC
Protection class	IP54
Colour	White
Dimension (axbxc)	100x100x75 mm
For use	Inside/Outside
Assembly method	On the ceiling
Application	INT/EXT
Made in	PRC
Other	Funkcja zmiany barwy światła 3000K/4000K/6000K ,



*Applies to the LED source used. **Luminaire luminous flux