





| | | | |
|------------------|-----------------------|--------------------|-------------------------|
| Power | 8 W | Voltage | 230 V |
| Luminous flux* | 1000 lm (360°) | Colour temperature | 3000/4000/6000 K |
| Light colour | CCT | Beam angle | 180 ° |
| Protection class | IP54 | | |



See more on dedicated page 




 User manual



 Declaration of Conformity

Technical data:

| | |
|---------------------------|---|
| Product code | SLI003037CCT_PW |
| Power | 8 W |
| Nominal current | 55 mA |
| Voltage | 230 V |
| Energy consumption | 8 kWh/1000h |
| Frequency | 50HZ Hz |
| Protection class | II |
| Power factor | 0.5 |
| Useful luminous flux* | 1000 lm (360°) |
| Luminous flux** | 800 lm (360°) |
| Light efficiency | 125 lm/W |
| Colour temperature | 3000/4000/6000 K |
| Light colour | CCT |
| Beam angle | 180 ° |
| RA | 80 |
| Light source included | + |
| Dimmable | No |
| Working temperature range | -20/+40 ° |
| Lifespan | 17000 h |
| Housing material | PLASTIC |
| Protection class | IP54 |
| Colour | White |
| Dimension (axbxc) | 200x100x75 mm |
| For use | Inside/Outside |
| Assembly method | On the ceiling |
| Application | INT/EXT |
| Made in | PRC |
| Other | Funkcja zmiany barwy światła 3000K/4000K/6000K , |



*Applies to the LED source used. **Luminaire luminous flux