

# SCATOLLO

SLI003038CCT\_PW

LED luminaire SCATOLLO with the possibility of changing the light color (CCT), with a power of 20 W, high light efficacy 125 lm/W. Thanks to the ability to change the color temperature (CCT) in the range 3000/4000/6000K, we can adjust the light color depending on our needs and preferences. It has a high IP54 rating, making it ideal for use in rooms with high humidity. The CCT function allows you to changes to the colour temperature of light (3000/4000/6000K). Designed for surface mounting.

CCT

IP54



|                           |                       |                    |                         |
|---------------------------|-----------------------|--------------------|-------------------------|
| Power                     | <b>20 W</b>           | Voltage            | <b>230 V</b>            |
| Luminous flux*            | <b>2500 lm (360°)</b> | Colour temperature | <b>3000/4000/6000 K</b> |
| Colour of light           | <b>CCT</b>            | Beam angle         | <b>180 °</b>            |
| Degree of protection (IP) | <b>IP54</b>           |                    |                         |

## Technical data

|                           |  |
|---------------------------|--|
| Code                      | SLI003038CCT_PW                                    |
| Power                     | 20 W   |
| Nominal current           | 140 mA   |
| Voltage                   | 230 V  |
| Energy consumption        | 20 kWh/1000h                                       |
| Frequency                 | 50HZ Hz  |
| Protection class          | II   |
| Power factor              | 0,5  |
| Useful luminous flux*     | 2500 lm (360°)                                     |
| Luminous flux**           | 2000 lm (360°)                                     |
| Lamp efficacy             | 125 lm/W   |
| Colour temperature        | 3000/4000/6000 K                                   |
| Colour of light           | CCT  |
| Beam angle                | 180 °  |
| RA                        | 80   |
| Light source included     | +  |
| Dimmable                  | No   |
| Working temperature range | -20/+40 °  |
| Lifespan                  | 17000 h  |
| Housing material          | PLASTIC  |
| Degree of protection (IP) | IP54   |
| Colour                    | White  |
| Dimension (AxBxC)         | 250x250x75 mm                                      |
| For use                   | Inside/Outside                                     |
| Assembly method           | On the ceiling                                     |
| Application               | INT/EXT  |
| Made in                   | PRC  |
| Other                     | Light color change function<br>3000K/4000K/6000K , |



## Related documents

[User manual](#)[Declaration of Conformity](#)[Photometric file](#)[3D model](#)

