



Power **12 W**

Voltage **230 V**

Colour temperature **6000 K**

Light colour **CW**

Beam angle **120 °**

Protection class **IP20**




 Declaration of Conformity



 Photometric file

Technical data:

|                              |               |
|------------------------------|---------------|
| Product code                 | SLI021021CW   |
| Power                        | 12 W          |
| Nominal current              | 60 mA         |
| Voltage                      | 230 V         |
| Energy consumption           | 12 kWh/1000h  |
| Frequency                    | 50HZ Hz       |
| Protection class             | II            |
| Power supply included        | +             |
| Luminous flux**              | 640 lm (360°) |
| Light efficiency             | 53 lm/W       |
| Colour temperature           | 6000 K        |
| Light colour                 | CW            |
| Beam angle                   | 120 °         |
| RA                           | 80            |
| Uniformity of color SDCM max | 5             |
| Dimmable                     | -             |
| Working temperature range    | -20/+40 °     |
| Lifespan                     | 17000 h       |
| Housing material             | Aluminum      |
| Protection class             | IP20          |
| Colour                       | White         |
| Dimension (axbxc)            | 160 mm        |
| Mounting hole                | fi 120 mm     |
| For use                      | Inside        |
| Assembly method              | Recessed      |
| Application                  | INT           |
| Made in                      | PRC           |



\*Applies to the LED source used. \*\*Luminaire luminous flux