




Power	<b>10 W</b>	Voltage	<b>230 V</b>
Luminous flux*	<b>850 lm (90°)</b>	Colour temperature	<b>6000 K</b>
Light colour	<b>CW</b>	Beam angle	<b>90 °</b>
Protection class	<b>IP20</b>		



 Declaration of Conformity



 Photometric file

**Technical data:**

Product code	SLI022006CW
Power	10 W
Nominal current	50 mA
Voltage	230 V
Energy efficiency classe	F
Energy consumption	10 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power supply included	+
Power factor	0.5
Useful luminous flux*	850 lm (90°)
Luminous flux**	850 lm (360°)
Light efficiency	85 lm/W
Colour temperature	6000 K
Light colour	CW
Beam angle	90 °
RA	80
Uniformity of color SDCM max	5
Dimmable	-
Working temperature range	-20/+40 °
Lifespan	17000 h
Housing material	TWORZYWO SZTUCZNE
Protection class	IP20
Colour	White
Dimension (axbxc)	150x80 mm
Mounting hole	130 mm
For use	Inside
Assembly method	Recessed
Application	INT
Made in	PRC



\*Applies to the LED source used. \*\*Luminaire luminous flux  
A version with CNBOP-PIB\* certificate is also available (valid only in Poland).