



Power	<b>25 W</b>	Voltage	<b>230 V</b>
Luminous flux*	<b>2000 lm (90°)</b>	Colour temperature	<b>4000 K</b>
Light colour	<b>Neutral white</b>	Beam angle	<b>90 °</b>
Protection class	<b>IP20</b>		



 Declaration of Conformity



 Photometric file



 3D model

**Technical data:**

Product code	SLI022009NW
Power	25 W
Nominal current	115 mA
Voltage	230 V
Energy efficiency classe	F
Energy consumption	25 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power supply included	+
Power factor	0.9
Useful luminous flux*	2000 lm (90°)
Luminous flux**	2000 lm (360°)
Light efficiency	80 lm/W
Colour temperature	4000 K
Light colour	Neutral white
Beam angle	90 °
RA	80
Uniformity of color SDCM max	5
Dimmable	-
Working temperature range	-20/+40 °
Lifespan	17000 h
Housing material	PLASTIC
Protection class	IP20
Colour	White
Dimension (axbxc)	230x100 mm
Mounting hole	210 mm
For use	Inside
Assembly method	Recessed
Application	INT
Made in	PRC



\*Applies to the LED source used. \*\*Luminaire luminous flux  
A version with CNBOP-PIB\* certificate is also available (valid only in Poland).