



Power	30 W	Voltage	230 V
Luminous flux*	2400 lm (90°)	Colour temperature	4000 K
Light colour	Neutral white	Beam angle	90 °
Protection class	IP44/IP20***		





 Declaration of Conformity



 Photometric file

Technical data:

Product code	SLI022010NW_IP44
Power	30 W
Nominal current	140 mA
Voltage	230 V
Energy efficiency classe	F
Energy consumption	30 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power supply included	+
Useful luminous flux*	2400 lm (90°)
Luminous flux**	2400 lm (360°)
Light efficiency	80 lm/W
Colour temperature	4000 K
Light colour	Neutral white
Beam angle	90 °
RA	80
Uniformity of color SDCM max	5
Dimmable	-
Working temperature range	-20/+40 °
Lifespan	17000 h
Housing material	PLASTIC
Protection class	IP44/IP20***
Colour	White
Dimension (axbxc)	230x103 mm
Mounting hole	210 mm
For use	Inside/Outside
Assembly method	Recessed
Made in	PRC



*Applies to the LED source used. **Luminaire luminous flux

A version with CNBOP-PIB* certificate is also available (valid only in Poland).***Degree of protection [IP] (from the bottom/ from the top)