

FIALE 3 STEPS

SLI022026WW_PW

Recessed lighting luminaire FIALE 3 STEPS, with a power of 12,5 W, high light efficacy 120 lm/W. The luminaire has three lighting modes: each on/off will change the mode. It has a high IP44 rating, making it ideal for use in rooms with high humidity. It shines with a warm light (3000K), which promotes relaxation and rest, making the illuminated room cosier. Designed for recessed mounting.

IP44

Power	12,5 W	Voltage	230 V
Luminous flux*	1500 lm (360°)	Colour temperature	3000 K
Colour of light	WW	Beam angle	120 °
Degree of protection (IP)	IP44		

Technical data

Code	SLI022026WW_PW
Power	12,5 W
Nominal current	75 mA
Voltage	230 V
Energy consumption	13 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power supply included	+
Power factor	0.5
Useful luminous flux*	1500 lm (360°)
Luminous flux**	1000 lm (360°)
Lamp efficacy	120 lm/W
Colour temperature	3000 K
Colour of light	WW
Beam angle	120 °
RA	80
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20/+40 °
Lifespan	17000 h
Housing material	PLASTIC
Degree of protection (IP)	IP44
Colour	White
Dimension (AxBxC)	148x37 mm
Mounting hole	128 mm
For use	Inside
Assembly method	Recessed
Application	INT
Made in	PRC

Logistics data

Quantity per pallet	1020 pcs.
Gross weight (1 pcs.)	0.262 kg

Related documents

 User manual Declaration of Conformity

