





Power	8 W	Voltage	230 V
Luminous flux*	700 lm (90°)	Colour temperature	2700-6500 K
Light colour	CCT	Beam angle	38°
IK	07	Protection class	IP65




See more on dedicated page 



 User manual



 Declaration of Conformity



 Photometric file

Technical data:

Product code	SLI022027
Power	8 W
Nominal current	40 mA
Voltage	230 V
Energy efficiency classe	F
Energy consumption	8 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power factor	0.5
Useful luminous flux*	700 lm (90°)
Luminous flux**	700 lm (360°)
Light efficiency	87 lm/W
Colour temperature	2700-6500 K
Light colour	CCT
Beam angle	38 °
RA	80
Light source included	+
Uniformity of color SDCM max	5
Dimmable	+
Working temperature range	-20/+40 °
Lifespan	50000 h
Housing material	Aluminum
IK	07
Protection class	IP65
Colour	White
Dimension (axbxc)	90x96 mm
Mounting hole	75 mm
For use	Inside
Assembly method	Recessed
Application	INT
Made in	PRC
Other	FIRE-RATED UK ,



*Applies to the LED source used. **Luminaire luminous flux

*Luminaire with the ability to change the color of light (3000K, 4000K, 6000K). Luminaire available on request.