

STREETOS

SLI027014NW_PW

Street luminaire STREETOS, with a power of 50 W, high light efficacy 152 lm/W. It is made of high-quality components, supported by a 5-year warranty. It has a very high degree of protection IP66, providing protection against the ingress of dust and water jets. IK9 class provides impact resistance. It shines with light of neutral - the most universal colour (4000K).



Power	50 W	Voltage	230 V
Luminous flux*	7600 lm (360°)	Colour temperature	4000 K
Colour of light	Neutral white	Beam angle	130/80 °
IK	9	Degree of protection (IP)	IP66


Technical data

Code	SLI027014NW_PW
Power	50 W
Nominal current	220 mA
Voltage	230 V
Energy consumption	50 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power factor	0.9
Useful luminous flux*	7600 lm (360°)
Luminous flux**	7200 lm (360°)
Lamp efficacy	152 lm/W
Colour temperature	4000 K
Colour of light	Neutral white
Beam angle	130/80 °
RA	70
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20/+40 °
Lifespan	50000 h
Housing material	Aluminum, PLASTIC
IK	9
Degree of protection (IP)	IP66
Colour	Gray
Dimension (AxBxC)	456x122x77 mm
Mounting hole	60 mm
For use	Outside
Assembly method	On a pole
Application	EXT
Made in	PRC
Other	100-265V ,




Related documents



 Declaration of Conformity



 Photometric file



Trwałe diody LED



Zabezpieczenie przetchw przeciwkośnie XUV



Klasa szczelności IP66



Zintegrowany regulowany uchwyty



5 lat gwarancji producenta	152 lm/W
IP66	IK09

