



Power	20 W	Voltage	230 V
Luminous flux*	3250 lm (120°)	Colour temperature	4000 K
Light colour	Neutral white	Beam angle	120 °
IK	9	Protection class	IP65



 Declaration of Conformity



 Photometric file

Technical data:

Product code	SLI028024NW
Power	20 W
Nominal current	140 mA
Voltage	230 V
Energy efficiency classe	C
Energy consumption	20 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power supply included	+
Useful luminous flux*	3250 lm (120°)
Luminous flux**	3000 lm (360°)
Light efficiency	163 lm/W
Luminous intensity	1000 cd
Colour temperature	4000 K
Light colour	Neutral white
Beam angle	120 °
RA	80
Uniformity of color SDCM max	3
Dimmable	-
Working temperature range	-20/+40 °
Lifespan	50000 h
Housing material	POLYCARBONATE
IK	9
Protection class	IP65
Colour	Gray/White
Dimension (axbxc)	600x72x70 mm
For use	Inside/Outside
Assembly method	On the ceiling/Suspended
Application	INT/EXT
Made in	PRC
Other	MAX 22 pcs per line ,



*Applies to the LED source used, **Luminaire luminous flux
Maximum number of luminaires to be connected in lines: 11 .