

# LIMEA GIGANT

SLI028024NW\_PW

Hermetic luminaire LIMEA GIGANT, with a power of 20 W, high light efficacy 163 lm/W. It is made of high-quality components, supported by a 5-year warranty. It has a very high degree of protection IP65, providing protection against the ingress of dust and water jets. IK10 class provides impact resistance. It shines with light of neutral - the most universal colour (4000K). Suitable for both surface and suspended mounting. The product is certified by the National Institute of Hygiene, so it can be used in rooms with high hygienic requirements.



|                 |                       |                           |               |
|-----------------|-----------------------|---------------------------|---------------|
| Power           | <b>20 W</b>           | Voltage                   | <b>230 V</b>  |
| Luminous flux*  | <b>3250 lm (360°)</b> | Colour temperature        | <b>4000 K</b> |
| Colour of light | <b>Neutral white</b>  | Beam angle                | <b>120 °</b>  |
| IK              | <b>10</b>             | Degree of protection (IP) | <b>IP65</b>   |

## Technical data

|                              |                           |
|------------------------------|---------------------------|
| Code                         | SLI028024NW_PW            |
| Power                        | 20 W                      |
| Nominal current              | 150 mA                    |
| Voltage                      | 230 V                     |
| Energy consumption           | 20 kWh/1000h              |
| Frequency                    | 50HZ Hz                   |
| Protection class             | I                         |
| Power supply included        | +                         |
| Useful luminous flux*        | 3250 lm (360°)            |
| Luminous flux**              | 3000 lm (360°)            |
| Lamp efficacy                | 163 lm/W                  |
| Luminous intensity           | 1000 cd                   |
| Colour temperature           | 4000 K                    |
| Colour of light              | Neutral white             |
| Beam angle                   | 120 °                     |
| RA                           | 80                        |
| Uniformity of color SDCM max | 3                         |
| Dimmable                     | No                        |
| Working temperature range    | -20/+40 °                 |
| Lifespan                     | 50000 h                   |
| Housing material             | POLYCARBONATE             |
| IK                           | 10                        |
| Degree of protection (IP)    | IP65                      |
| Colour                       | Gray/White                |
| Dimension (AxBxC)            | 600x72x70 mm              |
| For use                      | Inside/Outside            |
| Assembly method              | On the ceiling, Suspended |
| Application                  | INT/EXT                   |
| Made in                      | PRC                       |
| Other                        | MAX 22 pcs per line ,     |

## Logistics data

|                       |          |
|-----------------------|----------|
| Bulk packaging        | 20 pcs.  |
| Quantity per pallet   | 300 pcs. |
| Gross weight (1 pcs.) | 0.7 kg   |



## Related documents

 User manual Declaration of Conformity Photometric file

