





Power	<b>38 W</b>	Voltage	<b>230 V</b>
Luminous flux*	<b>6600 lm (120°)</b>	Colour temperature	<b>4000 K</b>
Light colour	<b>Neutral white</b>	Beam angle	<b>120 °</b>
IK	<b>09</b>	Protection class	<b>IP65</b>




See more on dedicated page 




 Declaration of Conformity



 Photometric file

**Technical data:**

Product code	SLI028025NW
Power	38 W
Nominal current	175 mA
Voltage	230 V
Energy efficiency classe	C
Energy consumption	38 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power supply included	+
Power factor	0.92
Useful luminous flux*	6600 lm (120°)
Luminous flux**	5900 lm (360°)
Light efficiency	174 lm/W
Luminous intensity	1800 cd
Colour temperature	4000 K
Light colour	Neutral white
Beam angle	120 °
RA	80
Uniformity of color SDCM max	3
Dimmable	-
Working temperature range	-20/+40 °
Lifespan	50000 h
Housing material	POLYCARBONATE
IK	09
Protection class	IP65
Colour	Gray/White
Dimension (axbxc)	1190x72x70 mm
For use	Inside/Outside
Assembly method	On the ceiling/Suspended
Application	INT/EXT
Made in	PRC
Other	MAX 22 pcs per line ,



\*Applies to the LED source used. \*\*Luminaire luminous flux

On request available version with the option of working in emergency mode. Maximum number of luminaires to be connected in lines: 11 .