


**CE**


Power	38 W	Voltage	230 V
Luminous flux*	6600 lm (360°)	Colour temperature	4000 K
Light colour	Neutral white	Beam angle	120 °
IK	10	Protection class	IP65

 User manual Declaration of Conformity

SLI028025NW_PW_AW

Technical data:

Product code	SLI028025NW_PW_AW
Power	38 W
Nominal current	180 mA
Voltage	230 V
Energy consumption	38 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power supply included	+
Power factor	0.98
Useful luminous flux*	6600 lm (360°)
Luminous flux**	5900 lm (360°)
Light efficiency	174 lm/W
Luminous intensity	2000 cd
Colour temperature	4000 K
Light colour	Neutral white
Beam angle	120 °
RA	80
Uniformity of color SDCM max	3
Dimmable	No
Working temperature range	-20/+40 °
Lifespan	50000 h
Housing material	POLYCARBONATE
IK	10
Protection class	IP65
Colour	Gray/White
Dimension (axbxc)	1190x72x70 mm
For use	Inside/Outside
Assembly method	natynkowy, zwieszany
Application	INT/EXT
Made in	PRC
Other	MAX 22 pcs per line, emergency module ,



*Applies to the LED source used. **Luminaire luminous flux