



Power	<b>52 W</b>	Voltage	<b>230 V</b>
Luminous flux*	<b>8900 lm (120°)</b>	Colour temperature	<b>6000 K</b>
Light colour	<b>CW</b>	Beam angle	<b>120 °</b>
IK	<b>10</b>	Protection class	<b>IP65</b>



 User manual



 Declaration of Conformity

**Technical data:**

Product code	SLI028026CW
Power	52 W
Nominal current	235 mA
Voltage	230 V
Energy efficiency classe	C
Energy consumption	52 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power supply included	+
Power factor	0.92
Useful luminous flux*	8900 lm (120°)
Luminous flux**	8000 lm (360°)
Light efficiency	171 lm/W
Luminous intensity	2500 cd
Colour temperature	6000 K
Light colour	CW
Beam angle	120 °
RA	80
Uniformity of color SDCM max	3
Dimmable	-
Working temperature range	-20/+40 °
Lifespan	50000 h
Housing material	POLYCARBONATE
IK	10
Protection class	IP65
Colour	Gray/White
Dimension (axbxc)	1490x72x70 mm
For use	Inside/Outside
Assembly method	On the ceiling/Suspended
Application	INT/EXT
Made in	PRC
Other	MAX 16 pcs per line ,



\*Applies to the LED source used. \*\*Luminaire luminous flux