

LIMEA GO

SLI028034NW

Hermetic luminaire LIMEA GO, with a power of 25 W, high light efficacy 120 lm/W. It has a very high degree of protection IP65, providing protection against the ingress of dust and water jets. IK07 class provides impact resistance. It shines with light of neutral - the most universal colour (4000K). Suitable for both surface and suspended mounting. The product is certified by the National Institute of Hygiene, so it can be used in rooms with high hygienic requirements.

IP65



IK07



Power	25 W	Voltage	230 V
Luminous flux*	3000 lm (120°)	Colour temperature	4000 K
Colour of light	Neutral white	Beam angle	120 °
IK	07	Degree of protection (IP)	IP65

Technical data

Code	SLI028034NW
Power	25 W
Nominal current	120 mA
Voltage	230 V
Energy efficiency class	E
Energy consumption	25 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power supply included	+
Power factor	0.9
Useful luminous flux*	3000 lm (120°)
Luminous flux**	3000 lm (360°)
Lamp efficacy	120 lm/W
Colour temperature	4000 K
Colour of light	Neutral white
Beam angle	120 °
RA	80
Light source included	+
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20/+40 °
Lifespan	17000 h
Housing material	plastic
IK	07
Degree of protection (IP)	IP65
Dimension (AxBxC)	600x60x52 mm
For use	Outside
Assembly method	On the ceiling, Suspended
Made in	PRC



Related documents



 Declaration of Conformity



 Photometric file

