




CE

Power	<b>40 W</b>	Voltage	<b>230 V</b>
Luminous flux*	<b>4600 lm (120°)</b>	Colour temperature	<b>4000 K</b>
Light colour	<b>Neutral white</b>	Beam angle	<b>100 °</b>
IK	<b>10</b>	Protection class	<b>IP44</b>



 User manual



 Declaration of Conformity



 Photometric file

**Technical data:**

Product code	SLI028036NW
Power	40 W
Nominal current	180 mA
Voltage	230 V
Energy consumption	40 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power factor	0.96
Useful luminous flux*	4600 lm (120°)
Luminous flux**	4600 lm (360°)
Light efficiency	115 lm/W
Luminous intensity	1700 cd
Colour temperature	4000 K
Light colour	Neutral white
Beam angle	100 °
RA	>80
Light source included	Yes
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20/+40 °
Lifespan	50000 h
Housing material	TWORZYWO SZTUCZNE - PC
IK	10
Protection class	IP44
Colour	White
Dimension (axbxc)	1200x110x60 mm
For use	Inside
Assembly method	natynkowy, zwieszany
Made in	PRC
Other	dane na moduł Fi use=4600 P=40W ,



\*Applies to the LED source used. \*\*Luminaire luminous flux