



Power **25 W**  
Luminous flux\* **4000 lm (360°)**  
Light colour **CW**  
IK **08**

Voltage **230 V**  
Colour temperature **6000 K**  
Beam angle **120 °**  
Protection class **IP65**



 User manual




 Declaration of Conformity



 Photometric file

#### Technical data:

|                              |                          |
|------------------------------|--------------------------|
| Product code                 | SLI028110CW_PW           |
| Power                        | 25 W                     |
| Nominal current              | 115 mA                   |
| Voltage                      | 230 V                    |
| Energy consumption           | 25 kWh/1000h             |
| Frequency                    | 50HZ Hz                  |
| Protection class             | II                       |
| Power supply included        | +                        |
| Power factor                 | 0.96                     |
| Useful luminous flux*        | 4000 lm (360°)           |
| Luminous flux**              | 3000 lm (360°)           |
| Light efficiency             | 160 lm/W                 |
| Colour temperature           | 6000 K                   |
| Light colour                 | CW                       |
| Beam angle                   | 120 °                    |
| RA                           | 80                       |
| Uniformity of color SDCM max | 5                        |
| Dimmable                     | No                       |
| Working temperature range    | -20/+40 °                |
| Lifespan                     | 26000 h                  |
| Housing material             | PC/PC                    |
| IK                           | 08                       |
| Protection class             | IP65                     |
| Colour                       | Gray                     |
| Dimension (axbxc)            | 600x64x60 mm             |
| For use                      | Inside/Outside           |
| Assembly method              | On the ceiling/Suspended |
| Application                  | INT/EXT                  |
| Made in                      | PRC                      |
| Other                        | MAX 22 pcs per line ,    |



\*Applies to the LED source used, \*\*Luminaire luminous flux