

LIMEA CONNECT

SLI028110NW_PW

Hermetic luminaire LIMEA CONNECT, with a power of 25 W, high light efficacy 160 lm/W. It has a very high degree of protection IP65, providing protection against the ingress of dust and water jets. IK08 class provides impact resistance. It shines with light of neutral - the most universal colour (4000K). Suitable for both surface and suspended mounting. The product is certified by the National Institute of Hygiene, so it can be used in rooms with high hygienic requirements.



Power	25 W	Voltage	230 V
Luminous flux*	4000 lm (360°)	Colour temperature	4000 K
Colour of light	Neutral white	Beam angle	120 °
IK	08	Degree of protection (IP)	IP65

Technical data


Code	SLI028110NW_PW
Power	25 W
Nominal current	115 mA
Voltage	230 V
Energy consumption	25 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power supply included	+
Power factor	0.96
Useful luminous flux*	4000 lm (360°)
Luminous flux**	3000 lm (360°)
Lamp efficacy	160 lm/W
Colour temperature	4000 K
Colour of light	Neutral white
Beam angle	120 °
RA	80
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20/+40 °
Lifespan	26000 h
Housing material	PC/PC
IK	08
Degree of protection (IP)	IP65
Colour	Gray
Dimension (AxBxC)	600x64x60 mm
For use	Inside/Outside
Assembly method	On the ceiling, Suspended
Application	INT/EXT
Made in	PRC
Other	MAX 22 pcs per line ,

Related documents



 User manual



 Declaration of Conformity



 Photometric file

