

120
lm/W




CE

| | | | |
|------------------|----------------------|--------------------|---------------|
| Power | 7 W | Voltage | 230 V |
| Luminous flux* | 840 lm (360°) | Colour temperature | 3000 K |
| Light colour | WW | Beam angle | 120 ° |
| Protection class | IP20 | | |



See more on dedicated page 



 User manual



 Declaration of Conformity

Technical data:

| | |
|------------------------------|--|
| Product code | SLI028203_PW |
| Power | 7 W |
| Nominal current | 60 mA |
| Voltage | 230 V |
| Energy consumption | 7 kWh/1000h |
| Frequency | 50HZ Hz |
| Protection class | II |
| Power supply included | + |
| Power factor | 0.5 |
| Useful luminous flux* | 840 lm (360°) |
| Luminous flux** | 700 lm (360°) |
| Light efficiency | 120 lm/W |
| Colour temperature | 3000 K |
| Light colour | WW |
| Beam angle | 120 ° |
| RA | >80 |
| Light source included | + |
| Uniformity of color SDCM max | 5 |
| Dimmable | No |
| Working temperature range | -20 +40 ° |
| Lifespan | 17000 h |
| Housing material | TWORZYWO SZTUCZNE |
| Protection class | IP20 |
| Colour | White |
| Dimension (axbxc) | 582x25x36 mm |
| For use | Inside |
| Assembly method | On the ceiling |
| Application | Inside |
| Made in | PRC |
| Other | Maks 15 sztuk w lini/Max 15 pcs per line , |



*Applies to the LED source used. **Luminaire luminous flux