

LIMEA GIGANT PRO

SLI028252NW_PW

Hermetic luminaire LIMEA GIGANT PRO, with a power of 27/37/47/58 W, high light efficacy 155 lm/W. It is made of high-quality components, supported by a 5-year warranty. It has a very high degree of protection IP66, providing protection against the ingress of dust and water jets. IK10 class provides impact resistance. It shines with light of neutral - the most universal colour (4000K). Suitable for both surface and suspended mounting. The product is certified by the National Institute of Hygiene, so it can be used in rooms with high hygienic requirements.



| | | | |
|-----------------|-----------------------|---------------------------|---------------|
| Power | 27/37/47/58 W | Voltage | 230 V |
| Luminous flux* | 9000 lm (360°) | Colour temperature | 4000 K |
| Colour of light | Neutral white | Beam angle | 120 ° |
| IK | 10 | Degree of protection (IP) | IP66 |

Technical data


| | |
|------------------------------|---------------------------|
| Code | SLI028252NW_PW |
| Power | 27/37/47/58 W |
| Nominal current | 255 mA |
| Voltage | 230 V |
| Energy consumption | 58 kWh/1000h |
| Frequency | 50HZ Hz |
| Protection class | I |
| Power supply included | + |
| Power factor | 0.9 |
| Useful luminous flux* | 9000 lm (360°) |
| Luminous flux** | 4200-8700 lm (360°) |
| Lamp efficacy | 155 lm/W |
| Colour temperature | 4000 K |
| Colour of light | Neutral white |
| Beam angle | 120 ° |
| RA | 80 |
| Uniformity of color SDCM max | 5 |
| Dimmable | No |
| Working temperature range | -20/+40 ° |
| Lifespan | 50000 h |
| Housing material | POLYCARBONATE |
| IK | 10 |
| Degree of protection (IP) | IP66 |
| Colour | Gray/White |
| Dimension (AxBxC) | 1500x80x68 mm |
| For use | Inside/Outside |
| Assembly method | On the ceiling, Suspended |
| Application | INT/EXT |
| Made in | PRC |
| Other | MAX 16 pcs per line , |

Related documents



 User manual



 Declaration of Conformity



 Photometric file

