




Power	<b>50 W</b>	Voltage	<b>230 V</b>
Luminous flux*	<b>4000 lm (120°)</b>	Colour temperature	<b>3000 K</b>
Light colour	<b>WW</b>	Beam angle	<b>100 °</b>
Protection class	<b>IP65</b>		



See more on dedicated page 



 Declaration of Conformity



 Photometric file

**Technical data:**

Product code	SLI029040WW
Power	50 W
Nominal current	230 mA
Voltage	230 V
Energy efficiency classe	F
Energy consumption	50 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power supply included	+
Power factor	0.9
Useful luminous flux*	4000 lm (120°)
Luminous flux**	3800/4000 lm (360°)
Light efficiency	76 lm/W
Colour temperature	3000 K
Light colour	WW
Beam angle	100 °
RA	80
Uniformity of color SDCM max	5
Dimmable	-
Working temperature range	-20/+40 °
Lifespan	17000 h
Housing material	Aluminum, GLASS
Protection class	IP65
Colour	Black
Dimension (axbxc)	160x205x31 mm
For use	Inside/Outside
Assembly method	On the ceiling
Application	INT/EXT
Made in	PRC



\*Applies to the LED source used. \*\*Luminaire luminous flux