


IP44



| | | | |
|------------------|-----------------------|--------------------|---------------|
| Power | 30 W | Voltage | 230 V |
| Luminous flux* | 2740 lm (120°) | Colour temperature | 3000 K |
| Light colour | WW | Beam angle | 100 ° |
| Protection class | IP44 | | |




See more on dedicated page 




 Declaration of Conformity



 Photometric file

Technical data:

| | |
|------------------------------|--------------------------|
| Product code | SLI029043WW_CZUJNIK |
| Power | 30 W |
| Nominal current | 130 mA |
| Voltage | 230 V |
| Energy efficiency classe | F |
| Energy consumption | 30 kWh/1000h |
| Frequency | 50HZ Hz |
| Protection class | I |
| Power supply included | + |
| Power factor | 0.9 |
| Useful luminous flux* | 2740 lm (120°) |
| Luminous flux** | 2600/2740 lm (360°) |
| Light efficiency | 87 lm/W |
| Colour temperature | 3000 K |
| Light colour | WW |
| Beam angle | 100 ° |
| RA | 80 |
| Uniformity of color SDCM max | 5 |
| Dimmable | - |
| Working temperature range | -20/+40 ° |
| Lifespan | 17000 h |
| Housing material | Aluminum, PLASTIC, GLASS |
| Protection class | IP44 |
| Colour | White |
| Dimension (axbxc) | 188x160x28 mm |
| For use | Inside/Outside |
| Assembly method | On the ceiling |
| Application | INT/EXT |
| Made in | PRC |



*Applies to the LED source used. **Luminaire luminous flux

Motion sensor PIR (sensor regulated, range: 2-10 m., operating time: 10 s. - 7 m., ambient light: 3 - 2000 LUX)