


IP44



Power	50 W	Voltage	230 V
Luminous flux*	4000 lm (120°)	Colour temperature	4000 K
Light colour	Neutral white	Beam angle	100 °
Protection class	IP44		




See more on dedicated page 





 Declaration of Conformity



 Photometric file

Technical data:

Product code	SLI029044NW_CZUJNIK
Power	50 W
Nominal current	240 mA
Voltage	230 V
Energy efficiency classe	F
Energy consumption	50 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power factor	0.9
Useful luminous flux*	4000 lm (120°)
Luminous flux**	3850/4000 lm (360°)
Light efficiency	77 lm/W
Colour temperature	4000 K
Light colour	Neutral white
Beam angle	100 °
RA	80
Uniformity of color SDCM max	5
Dimmable	-
Working temperature range	-20/+40 °
Lifespan	17000 h
Housing material	Aluminum, PLASTIC, GLASS
Protection class	IP44
Colour	White
Dimension (axbxc)	212x206x35 mm
For use	Inside/Outside
Assembly method	On the ceiling
Application	INT/EXT
Made in	PRC



*Applies to the LED source used. **Luminaire luminous flux

Motion sensor PIR (sensor regulated, range: 2-10 m., operating time: 10 s. - 7 m., ambient light: 3 - 2000 LUX)