


IP65



Power	24 W	Voltage	230 V
Luminous flux*	2260 lm (120°)	Colour temperature	3000-6500 K
Light colour	CCT/RGB	Beam angle	120 °
IK	07	Protection class	IP65




 User manual



 Declaration of Conformity

Technical data:

Product code	SLI029045
Power	24 W
Nominal current	115 mA
Voltage	230 V
Energy efficiency classe	F
Energy consumption	24 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power supply included	+
Power factor	0.9
Useful luminous flux*	2260 lm (120°)
Luminous flux**	1800 lm (360°)
Light efficiency	75 lm/W
Colour temperature	3000-6500 K
Light colour	CCT/RGB
Beam angle	120 °
RA	80
Uniformity of color SDCM max	5
Dimmable	SMART
Working temperature range	-20/+40 °
Lifespan	17000 h
Housing material	Aluminum
IK	07
Protection class	IP65
Colour	Black
Dimension (axbxc)	155 x 146 x 40 mm
For use	Inside/Outside
Assembly method	On the ceiling
Application	INT/EXT
Other	Variable temperature. Color 2700K / 4000K / 6000K ,



*Applies to the LED source used. **Luminaire luminous flux