

NOCTIS LUX 3

SLI029049CW_CZUJNIK_PW

Floodlight NOCTIS LUX 3, with a power of 20 W, high light efficacy 103 lm/W. It has a high IP44 rating, making it ideal for use in areas of high humidity. IK07 class provides impact resistance. It shines with a cold light (6000K). Designed for surface mounting.

IP44

IK07



Power	20 W
Luminous flux*	2050 lm (120°)
Colour of light	CW
IK	07

Voltage	230 V
Colour temperature	6000 K
Beam angle	100 °
Degree of protection (IP)	IP44

Technical data

Code	SLI029049CW_CZUJNIK_PW
Power	20 W
Nominal current	90 mA
Voltage	230 V
Energy consumption	20 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power supply included	+
Power factor	0.9
Useful luminous flux*	2050 lm (120°)
Luminous flux**	2050 lm (360°)
Lamp efficacy	103 lm/W
Colour temperature	6000 K
Colour of light	CW
Beam angle	100 °
RA	>70
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20/+40 °
Lifespan	17000 h
Housing material	Aluminum, GLASS
IK	07
Degree of protection (IP)	IP44
Colour	Black
Dimension (AxBxC)	120x170x53 mm
For use	Outside
Assembly method	On the ceiling
Application	EXT
Made in	PRC

Logistics data

Bulk packaging	40 pcs.
Quantity per pallet	960 pcs.
Gross weight (1 pcs.)	0.356 kg



Related documents

 Declaration of Conformity Photometric file

