

NOCTIS LUX 3

SLI029050CW_CZUJNIK_PW

Floodlight NOCTIS LUX 3, with a power of 30 W. It has a high IP44 rating, making it ideal for use in areas of high humidity. IK07 class provides impact resistance. It shines with a cold light (6000K). Designed for surface mounting.

IP44

IK07



Power	30 W	Voltage	230 V
Luminous flux*	2900 lm (120°)	Colour temperature	6000 K
Colour of light	CW	Beam angle	100 °
IK	07	Degree of protection (IP)	IP44


Technical data

Code	SLI029050CW_CZUJNIK_PW
Power	30 W
Nominal current	130 mA
Voltage	230 V
Energy consumption	30 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power supply included	+
Power factor	0.9
Useful luminous flux*	2900 lm (120°)
Luminous flux**	2900 lm (360°)
Lamp efficacy	97 lm/W
Colour temperature	6000 K
Colour of light	CW
Beam angle	100 °
RA	>70
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20/+40 °
Lifespan	17000 h
Housing material	Aluminum, GLASS
IK	07
Degree of protection (IP)	IP44
Colour	Black
Dimension (AxBxC)	150x190x53 mm
For use	Outside
Assembly method	On the ceiling
Application	EXT
Made in	PRC



Related documents



 Declaration of Conformity



 Photometric file

