



|                |                        |                    |               |
|----------------|------------------------|--------------------|---------------|
| Power          | <b>200 W</b>           | Voltage            | <b>230 V</b>  |
| Luminous flux* | <b>17500 lm (120°)</b> | Colour temperature | <b>4000 K</b> |
| Light colour   | <b>Neutral white</b>   | Beam angle         | <b>85 °</b>   |
| IK             | <b>10</b>              | Protection class   | <b>IP65</b>   |



 User manual



 Declaration of Conformity



 Photometric file

#### Technical data:

|                              |                  |
|------------------------------|------------------|
| Product code                 | SLI029057NW_PW   |
| Power                        | 200 W            |
| Nominal current              | 850 mA           |
| Voltage                      | 230 V            |
| Energy efficiency classe     | F                |
| Energy consumption           | 200 kWh/1000h    |
| Frequency                    | 50HZ Hz          |
| Protection class             | I                |
| Power factor                 | 0.99             |
| Useful luminous flux*        | 17500 lm (120°)  |
| Luminous flux**              | 17500 lm (360°)  |
| Light efficiency             | 88 lm/W          |
| Luminous intensity           | 10500 cd         |
| Colour temperature           | 4000 K           |
| Light colour                 | Neutral white    |
| Beam angle                   | 85 °             |
| RA                           | >80              |
| Light source included        | +                |
| Uniformity of color SDCM max | 5                |
| Dimmable                     | -                |
| Working temperature range    | -20 to +40 °     |
| Lifespan                     | 50000 h          |
| Housing material             | Aluminum+PC LENS |
| IK                           | 10               |
| Protection class             | IP65             |
| Colour                       | Gray             |
| Dimension (axbxc)            | 410x290x30 mm    |
| For use                      | Outside          |
| Assembly method              | On the ceiling   |
| Application                  | EXT              |
| Made in                      | PRC              |



\*Applies to the LED source used. \*\*Luminaire luminous flux