

# NOCTIS LUX 4

SLI029069WW\_PW

Floodlight NOCTIS LUX 4, with a power of 100 W. It has a very high degree of protection IP65, providing protection against the ingress of dust and water jets. IK07 class provides impact resistance. It shines with a warm light (3000K). Designed for surface mounting.

IP65

IK07



Power	<b>100 W</b>	Voltage	<b>230 V</b>
Luminous flux*	<b>8700 lm (120°)</b>	Colour temperature	<b>3000 K</b>
Colour of light	<b>WW</b>	Beam angle	<b>100 °</b>
IK	<b>07</b>	Degree of protection (IP)	<b>IP65</b>

## Technical data

---

Code	SLI029069WW_PW
Power	100 W
Nominal current	425 mA
Voltage	230 V
Energy consumption	100 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power supply included	+
Power factor	0.9
Useful luminous flux*	8700 lm (120°)
Luminous flux**	8700 lm (360°)
Lamp efficacy	87 lm/W
Colour temperature	3000 K
Colour of light	WW
Beam angle	100 °
RA	>70
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20/+40 °
Lifespan	17000 h
Housing material	Aluminum, GLASS
IK	07
Degree of protection (IP)	IP65
Colour	White
Dimension (AxBxC)	251x207x26 mm
For use	Outside
Assembly method	On the ceiling
Application	EXT
Made in	PRC

