

# NOCTIS LUX 4

SLI029071NW\_CZUJNIK\_PW

Floodlight NOCTIS LUX 4, with a power of 20 W. It has a high IP44 rating, making it ideal for use in areas of high humidity. IK07 class provides impact resistance. It shines with light of neutral - the most universal colour (4000K). Designed for surface mounting.



Power	<b>20 W</b>	Voltage	<b>230 V</b>
Luminous flux*	<b>1650 lm (120°)</b>	Colour temperature	<b>4000 K</b>
Colour of light	<b>Neutral white</b>	Beam angle	<b>100 °</b>
IK	<b>07</b>	Degree of protection (IP)	<b>IP44</b>

## Technical data


---

Code	SLI029071NW_CZUJNIK_PW
Power	20 W
Nominal current	95 mA
Voltage	230 V
Energy consumption	20 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power supply included	+
Power factor	0.9
Useful luminous flux*	1650 lm (120°)
Luminous flux**	1650 lm (360°)
Lamp efficacy	83 lm/W
Colour temperature	4000 K
Colour of light	Neutral white
Beam angle	100 °
RA	>70
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20/+40 °
Lifespan	17000 h
Housing material	Aluminum, GLASS
IK	07
Degree of protection (IP)	IP44
Colour	Black
Dimension (AxBxC)	116x174x53 mm
For use	Outside
Assembly method	On the ceiling
Application	EXT
Made in	PRC
Other	PIR motion sensor ,


## Related documents

---



 User manual



 Declaration of Conformity

