

NOCTIS LUX 4

SLI029071WW_PW

Floodlight NOCTIS LUX 4, with a power of 20 W. It has a very high degree of protection IP65, providing protection against the ingress of dust and water jets. IK07 class provides impact resistance. It shines with a warm light (3000K). Designed for surface mounting.

IP65

IK07



Power	20 W	Voltage	230 V
Luminous flux*	1650 lm (120°)	Colour temperature	3000 K
Colour of light	WW	Beam angle	100 °
IK	07	Degree of protection (IP)	IP65

Technical data


Code	SLI029071WW_PW
Power	20 W
Nominal current	95 mA
Voltage	230 V
Energy consumption	20 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power supply included	+
Power factor	0.9
Useful luminous flux*	1650 lm (120°)
Luminous flux**	1650 lm (360°)
Lamp efficacy	83 lm/W
Colour temperature	3000 K
Colour of light	WW
Beam angle	100 °
RA	>70
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20/+40 °
Lifespan	17000 h
Housing material	Aluminum, GLASS
IK	07
Degree of protection (IP)	IP65
Colour	Black
Dimension (AxBxC)	116x92x24 mm
For use	Outside
Assembly method	On the ceiling
Application	EXT
Made in	PRC

Related documents



 User manual



 Declaration of Conformity

