

# NOCTIS LUX 4

SLI029076WW\_PW

Floodlight NOCTIS LUX 4, with a power of 30 W. It has a very high degree of protection IP65, providing protection against the ingress of dust and water jets. IK07 class provides impact resistance. It shines with a warm light (3000K). Designed for surface mounting.



Power	<b>30 W</b>	Voltage	<b>230 V</b>
Luminous flux*	<b>2500 lm (120°)</b>	Colour temperature	<b>3000 K</b>
Colour of light	<b>WW</b>	Beam angle	<b>100 °</b>
IK	<b>07</b>	Degree of protection (IP)	<b>IP65</b>

## Technical data


---

Code	SLI029076WW_PW
Power	30 W
Nominal current	135 mA
Voltage	230 V
Energy consumption	30 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power supply included	+
Power factor	0.9
Useful luminous flux*	2500 lm (120°)
Luminous flux**	2500 lm (360°)
Lamp efficacy	83 lm/W
Colour temperature	3000 K
Colour of light	WW
Beam angle	100 °
RA	>70
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20/+40 °
Lifespan	17000 h
Housing material	Aluminum, GLASS
IK	07
Degree of protection (IP)	IP65
Colour	White
Dimension (AxBxC)	141x107x25 mm
For use	Outside
Assembly method	On the ceiling
Application	EXT
Made in	PRC

## Related documents

---



 User manual

