





| | | | |
|----------------|----------------------|--------------------|---------------|
| Power | 9 W | Voltage | 230 V |
| Luminous flux* | 810 lm (120°) | Colour temperature | 3000 K |
| Light colour | WW | Beam angle | 120 ° |
| IK | 08 | Protection class | IP65 |



 User manual



 Declaration of Conformity



 Photometric file

Technical data:

| | |
|------------------------------|----------------|
| Product code | SLI031022WW |
| Power | 9 W |
| Nominal current | 70 mA |
| Voltage | 230 V |
| Energy efficiency classe | F |
| Energy consumption | 9 kWh/1000h |
| Frequency | 50HZ Hz |
| Protection class | II |
| Power factor | 0.5 |
| Useful luminous flux* | 810 lm (120°) |
| Luminous flux** | 810 lm (360°) |
| Light efficiency | 90 lm/W |
| Colour temperature | 3000 K |
| Light colour | WW |
| Beam angle | 120 ° |
| RA | 80 |
| Uniformity of color SDCM max | 5 |
| Dimmable | - |
| Working temperature range | -20/+40 ° |
| Lifespan | 17000 h |
| Housing material | PLASTIC |
| IK | 08 |
| Protection class | IP65 |
| Colour | White |
| Dimension (axbxc) | 175x65 mm |
| For use | Inside/Outside |
| Assembly method | On the ceiling |
| Application | INT/EXT |
| Made in | PRC |



*Applies to the LED source used. **Luminaire luminous flux