



|                |                       |                    |                         |
|----------------|-----------------------|--------------------|-------------------------|
| Power          | <b>18 W</b>           | Voltage            | <b>230 V</b>            |
| Luminous flux* | <b>1800 lm (120°)</b> | Colour temperature | <b>2700/4000/6000 K</b> |
| Light colour   | <b>CCT</b>            | Beam angle         | <b>120 °</b>            |
| IK             | <b>10</b>             | Protection class   | <b>IP65</b>             |



See more on dedicated page 



 Declaration of Conformity



 Photometric file



 3D model

**Technical data:**

|                              |   |
|------------------------------|---|
| Product code                 | SLI031028CCT  |
| Power                        | 18 W  |
| Nominal current              | 80 mA   |
| Voltage                      | 230 V   |
| Energy efficiency classe     | F   |
| Energy consumption           | 18 kWh/1000h  |
| Frequency                    | 50HZ Hz   |
| Protection class             | II  |
| Power supply included        | +   |
| Power factor                 | 0.9   |
| Useful luminous flux*        | 1800 lm (120°)                                      |
| Luminous flux**              | 1800 lm (360°)                                      |
| Light efficiency             | 100 lm/W  |
| Luminous intensity           | 600 cd  |
| Colour temperature           | 2700/4000/6000 K                                    |
| Light colour                 | CCT   |
| Beam angle                   | 120 °   |
| RA                           | 80  |
| Light source included        | +   |
| Uniformity of color SDCM max | 5   |
| Dimmable                     | No  |
| Working temperature range    | -20/+40 °   |
| Lifespan                     | 50000 h   |
| Housing material             | PC  |
| IK                           | 10  |
| Protection class             | IP65  |
| Colour                       | White   |
| Dimension (axbxc)            | 330X79 mm   |
| For use                      | Inside/Outside                                      |
| Assembly method              | On the ceiling                                      |
| Application                  | INT/EXT   |
| Made in                      | PRC   |
| Other                        | Variable temperature. Color 2700K / 4000K / 6000K , |



\*Applies to the LED source used. \*\*Luminaire luminous flux  
\*CCT - variable color temperature (3000K, 4000K, 6000K)