


IP44



Power	<b>18 W</b>	Voltage	<b>230 V</b>
Luminous flux*	<b>1600 lm (120°)</b>	Colour temperature	<b>4000 K</b>
Light colour	<b>Neutral white</b>	Beam angle	<b>120 °</b>
IK	<b>10</b>	Protection class	<b>IP44</b>




See more on dedicated page 



 Declaration of Conformity



 Photometric file



 3D model

**Technical data:**

Product code	SLI031031NW
Power	18 W
Nominal current	150 mA
Voltage	230 V
Energy efficiency classe	F
Energy consumption	18 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power supply included	+
Power factor	0.5
Useful luminous flux*	1600 lm (120°)
Luminous flux**	1600 lm (360°)
Light efficiency	88 lm/W
Colour temperature	4000 K
Light colour	Neutral white
Beam angle	120 °
RA	80
Uniformity of color SDCM max	5
Dimmable	-
Working temperature range	-20/+40 °
Lifespan	17000 h
Housing material	PLASTIC
IK	10
Protection class	IP44
Colour	White
Dimension (axbxc)	330x330x60 mm
For use	Inside/Outside
Assembly method	On the ceiling
Application	INT/EXT
Made in	PRC



\*Applies to the LED source used. \*\*Luminaire luminous flux  
For request available version with motion sensor (SLI031031NW\_CZUJNIK).