



IP54 117  
lm/W




Power	<b>24 W</b>	Voltage	<b>230 V</b>
Luminous flux*	<b>2800 lm (360°)</b>	Colour temperature	<b>3000 K</b>
Light colour	<b>WW</b>	Beam angle	<b>115 °</b>
IK	<b>04</b>	Protection class	<b>IP54</b>



 User manual





 Declaration of Conformity



 Photometric file

**Technical data:**

Product code	SLI031035WW_PW
Power	24 W
Nominal current	175 mA
Voltage	230 V
Energy efficiency classe	E
Energy consumption	24 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power supply included	+
Power factor	0.6
Useful luminous flux*	2800 lm (360°)
Luminous flux**	1650 lm (360°)
Light efficiency	117 lm/W
Luminous intensity	1050 cd
Colour temperature	3000 K
Light colour	WW
Beam angle	115 °
RA	>80
Light source included	+
Uniformity of color SDCM max	5
Dimmable	-
Working temperature range	-20 +40 °
Lifespan	17000 h
Housing material	TWORZYWO SZTUCZNE
IK	04
Protection class	IP54
Colour	White
Dimension (axbxc)	Ø 320 x 52 mm
For use	Inside/Outside
Assembly method	On the ceiling
Application	Inside/Outside
Made in	PRC



\*Applies to the LED source used. \*\*Luminaire luminous flux