


104  
lm/W




Power	<b>25 W</b>	Voltage	<b>230 V</b>
Luminous flux*	<b>2600 lm (90°)</b>	Colour temperature	<b>3000 K</b>
Light colour	<b>WW</b>	Beam angle	<b>36, 60 °</b>
UGR	<b>&gt;20</b>	Protection class	<b>IP20</b>




See more on dedicated page 



 User manual




 Declaration of Conformity



 Photometric file

**Technical data:**

Product code	SLI033019WW
Power	25 W
Nominal current	120 mA
Voltage	230 V
Energy efficiency classe	E
Energy consumption	25 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power supply included	+
Manufacturer of power supply	LIFUD
Power factor	0,9
Useful luminous flux*	2600 lm (90°)
Luminous flux**	2600 lm (360°)
Light efficiency	104 lm/W
Luminous intensity	6100 cd
Colour temperature	3000 K
Light colour	WW
Beam angle	36, 60 °
UGR	>20
RA	80
Light source included	+
Producer of LED diodes	SANAN
Uniformity of color SDCM max	5
Dimmable	-
Working temperature range	-20/+40 °
Lifespan	17000 h
Housing material	Aluminum, PLASTIC
Protection class	IP20
Colour	White
Dimension (axbxc)	170 x 160 x 74 mm
For use	Inside
Assembly method	On 3-circuit system
Application	INT
Made in	PRC



\*Applies to the LED source used. \*\*Luminaire luminous flux  
Includes reflectors that allow you to change the beam angle (36°, 60°).