





|                    |                 |                  |              |
|--------------------|-----------------|------------------|--------------|
| Power              | <b>6,5-20 W</b> | Voltage          | <b>230 V</b> |
| Colour temperature | <b>3000 K</b>   | Light colour     | <b>WW</b>    |
| Beam angle         | <b>36, 60 °</b> | Protection class | <b>IP20</b>  |




See more on dedicated page 



 User manual



 Declaration of Conformity



 Photometric file



Technical data:

|                              |                                      |
|------------------------------|--------------------------------------|
| Product code                 | SLI033023WW_PW                       |
| Power                        | 6,5-20 W                             |
| Nominal current              | 90 mA                                |
| Voltage                      | 230 V                                |
| Energy consumption           | 20 kWh/1000h                         |
| Frequency                    | 50HZ Hz                              |
| Protection class             | II                                   |
| Power supply included        | Yes                                  |
| Power factor                 | 0.9                                  |
| Useful luminous flux*        | 2300 lm (360°)                       |
| Luminous flux**              | 600-1700 lm (360°)                   |
| Light efficiency             | 115 lm/W                             |
| Luminous intensity           | 3800 cd                              |
| Colour temperature           | 3000 K                               |
| Light colour                 | WW                                   |
| Beam angle                   | 36, 60 °                             |
| RA                           | >90                                  |
| Light source included        | Yes                                  |
| Uniformity of color SDCM max | 5                                    |
| Dimmable                     | No                                   |
| Working temperature range    | -20/+40 °                            |
| Lifespan                     | 50000 h                              |
| Housing material             | Aluminum, PLASTIC                    |
| Protection class             | IP20                                 |
| Colour                       | Black                                |
| Dimension (axbxc)            | 75x78x110 mm                         |
| For use                      | Inside                               |
| Assembly method              | na szynoprzewód                      |
| Application                  | Inside                               |
| Made in                      | PRC                                  |
| Other                        | DIP SWITCH - regulowana moc oprawy , |



\*Applies to the LED source used. \*\*Luminaire luminous flux