

# PAVA 2

SLI033030WW\_PW

On track luminaire PAVA 2, with power regulation on the power supply (19-42 W), high light efficacy 107 lm/W. The rotating ring allows you to smoothly changing the beam angle in the range from 20° to 45°. It is made of high-quality components, supported by a 5-year warranty. It also stands out for its very high colour rendering index RA>90. It shines with a warm light (3000K), which promotes relaxation and rest, making the illuminated room cosier. Designed to be mounted on a track.



Power **19-42 W**  
Colour temperature **3000 K**  
Beam angle **20-45 °**

Voltage **230 V**  
Colour of light **WW**  
Degree of protection (IP) **IP20**

## Technical data


---

Code	SLI033030WW_PW
Power	19-42 W
Nominal current	185 mA
Voltage	230 V
Energy consumption	42 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power supply included	Yes
Power factor	0.9
Useful luminous flux*	4500 lm (360°)
Luminous flux**	1800-3200 lm (360°)
Lamp efficacy	107 lm/W
Luminous intensity	8900 cd
Colour temperature	3000 K
Colour of light	WW
Beam angle	20-45 °
RA	>90
Light source included	Yes
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20/+40 °
Lifespan	50000 h
Housing material	Aluminum, PLASTIC
Degree of protection (IP)	IP20
Colour	White
Dimension (AxBxC)	96x192x231 mm
For use	Inside
Assembly method	on track
Application	Inside
Made in	PRC
Other	DIP SWITCH - adjustable power of luminaire ,

## Related documents

---



 User manual



 Declaration of Conformity



 Photometric file



 3D model

