


103  
lm/W




Power	<b>32 W</b>	Voltage	<b>230 V</b>
Luminous flux*	<b>3300 lm (120°)</b>	Colour temperature	<b>4000 K</b>
Light colour	<b>Neutral white</b>	Beam angle	<b>120 °</b>
IK	<b>06</b>	Protection class	<b>IP20</b>



 User manual



 Declaration of Conformity



 Photometric file

**Technical data:**

Product code	SLI035014NW
Power	32 W
Nominal current	154 mA
Voltage	230 V
Energy efficiency classe	E
Energy consumption	32 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power factor	0.9
Useful luminous flux*	3300 lm (120°)
Luminous flux**	3240 lm (360°)
Light efficiency	103 lm/W
Colour temperature	4000 K
Light colour	Neutral white
Beam angle	120 °
RA	80
Uniformity of color SDCM max	5
Dimmable	-
Working temperature range	-20/+40 °
Lifespan	17000 h
Housing material	Aluminum, PLASTIC
IK	06
Protection class	IP20
Colour	White
Dimension (axbxc)	295x1195x10 mm
Mounting hole	275x1175 mm
For use	Inside
Assembly method	Recessed/On the ceiling/Suspended
Application	INT
Made in	PRC



\*Applies to the LED source used. \*\*Luminaire luminous flux  
Also available as SMART, DALI, DIM and version with CNBOP-PIB\* certificate (valid only in Poland).