



Power	44 W	Voltage	230 V
Luminous flux*	5300 lm (360°)	Colour temperature	4000 K
Light colour	Neutral white	Beam angle	70°
UGR	<16	IK	06



 Declaration of Conformity



 Photometric file

Technical data:

Product code	SLI035050NW
Power	44 W
Nominal current	200 mA
Voltage	230 V
Energy efficiency classe	C
Energy consumption	44 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power supply included	+
Manufacturer of power supply	PHILIPS
Power factor	0,9
Useful luminous flux*	5300 lm (360°)
Luminous flux**	5300 lm (360°)
Light efficiency	120 lm/W
Colour temperature	4000 K
Light colour	Neutral white
Beam angle	70 °
UGR	<16
RA	80
Producer of LED diodes	PHILIPS
Uniformity of color SDCM max	5
Dimmable	-
Working temperature range	-20/+40 °
Lifespan	50000 h
Housing material	STEEL
IK	06
Protection class	IP20
Colour	White
Dimension (axbxc)	597x597x40 mm
Mounting hole	565x565 mm
For use	Inside
Assembly method	Recessed/On the ceiling/Suspended
Application	INT
Made in	PRC



*Applies to the LED source used. **Luminaire luminous flux
Also available as DALI, DIM, DIMRF.