


## ALGINE BACKLIGHT 30W led panel



CE

Power	<b>30 W</b>	Voltage	<b>230 V</b>
Luminous flux*	<b>4300 lm (360°)</b>	Colour temperature	<b>6000 K</b>
Colour of light	<b>CW</b>	Beam angle	<b>120 °</b>
Degree of protection (IP)	<b>IP20</b>		



See more on dedicated page 



 Declaration of Conformity

**Technical data:**

Code	SLI035055CW_PW
Power	30 W
Nominal current	132 mA
Voltage	230 V
Energy efficiency class	E
Energy consumption	30 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power supply included	+
Power factor	0.9
Useful luminous flux*	4300 lm (360°)
Luminous flux**	3600 lm (360°)
Lamp efficacy	143 lm/W
Colour temperature	6000 K
Colour of light	CW
Beam angle	120 °
RA	>80
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20/+40 °
Lifespan	50000 h
Housing material	Aluminum/Steel/TWORZYWO SZTUCZNE
Degree of protection (IP)	IP20
Colour	White
Dimension (AxBxC)	595x595x28 mm
Weight	1.5 kg
For use	Inside
Assembly method	NATYNK/PODTYNK
Application	INT
Made in	PRC



\*applies to the LED source used, \*\*Luminaire luminous flux