





CE

|                  |                       |                    |               |
|------------------|-----------------------|--------------------|---------------|
| Power            | <b>30 W</b>           | Voltage            | <b>230 V</b>  |
| Luminous flux*   | <b>4300 lm (360°)</b> | Colour temperature | <b>4000 K</b> |
| Light colour     | <b>Neutral white</b>  | Beam angle         | <b>120 °</b>  |
| Protection class | <b>IP20</b>           |                    |               |



See more on dedicated page 



 User manual



 Declaration of Conformity



 Photometric file

Technical data:

|                              |                                  |
|------------------------------|----------------------------------|
| Product code                 | SLI035055NW_PW                   |
| Power                        | 30 W                             |
| Nominal current              | 132 mA                           |
| Voltage                      | 230 V                            |
| Energy consumption           | 30 kWh/1000h                     |
| Frequency                    | 50HZ Hz                          |
| Protection class             | I                                |
| Power supply included        | +                                |
| Power factor                 | 0.9                              |
| Useful luminous flux*        | 4300 lm (360°)                   |
| Luminous flux**              | 3600 lm (360°)                   |
| Light efficiency             | 143 lm/W                         |
| Colour temperature           | 4000 K                           |
| Light colour                 | Neutral white                    |
| Beam angle                   | 120 °                            |
| RA                           | >80                              |
| Uniformity of color SDCM max | 5                                |
| Dimmable                     | No                               |
| Working temperature range    | -20/+40 °                        |
| Lifespan                     | 50000 h                          |
| Housing material             | Aluminum/Steel/TWORZYWO SZTUCZNE |
| Protection class             | IP20                             |
| Colour                       | White                            |
| Dimension (axbxc)            | 595x595x28 mm                    |
| For use                      | Inside                           |
| Assembly method              | natynkowy, podtynkowy            |
| Application                  | INT                              |
| Made in                      | PRC                              |



\*Applies to the LED source used. \*\*Luminaire luminous flux