

ALGINE BACKLIGHT

SLI035059CW_PW

LED panel ALGINE BACKLIGHT, with a power of 40 W, high light efficacy 120 lm/W. It shines with a cold light colour (6000K), which is suitable for rooms where we need to be most focused and concentrated, such as technical workstations. Suitable for both surface and recessed mounting. The product is certified by the National Institute of Hygiene, so it can be used in rooms with high hygienic requirements.



| | | | |
|---------------------------|-----------------------|--------------------|---------------|
| Power | 40 W | Voltage | 230 V |
| Luminous flux* | 4800 lm (360°) | Colour temperature | 6000 K |
| Colour of light | CW | Beam angle | 120 ° |
| Degree of protection (IP) | IP20 | | |


Technical data

| | |
|------------------------------|--------------------------|
| Code | SLI035059CW_PW |
| Power | 40 W |
| Nominal current | 173 mA |
| Voltage | 230 V |
| Energy consumption | 40 kWh/1000h |
| Frequency | 50HZ Hz |
| Protection class | I |
| Power supply included | + |
| Power factor | 0.9 |
| Useful luminous flux* | 4800 lm (360°) |
| Luminous flux** | 3800 lm (360°) |
| Lamp efficacy | 120 lm/W |
| Colour temperature | 6000 K |
| Colour of light | CW |
| Beam angle | 120 ° |
| RA | >80 |
| Uniformity of color SDCM max | 5 |
| Dimmable | No |
| Working temperature range | -20/+40 ° |
| Lifespan | 26000 h |
| Housing material | Aluminum/Steel/Plastic |
| Degree of protection (IP) | IP20 |
| Colour | White |
| Dimension (AxBxC) | 295x1195x25 mm |
| For use | Inside |
| Assembly method | On the ceiling, Recessed |
| Application | INT |
| Made in | PRC |




Related documents



 User manual



 Declaration of Conformity



 Photometric file

