

# ALGINE BACKLIGHT

SLI035059WW\_PW

LED panel ALGINE BACKLIGHT, with a power of 40 W, high light efficacy 115 lm/W. It shines with a warm light (3000K), which promotes relaxation and rest, making the illuminated room cosier. Suitable for both surface and recessed mounting. The product is certified by the National Institute of Hygiene, so it can be used in rooms with high hygienic requirements.



Power	<b>40 W</b>	Voltage	<b>230 V</b>
Luminous flux*	<b>4600 lm (360°)</b>	Colour temperature	<b>3000 K</b>
Colour of light	<b>WW</b>	Beam angle	<b>120 °</b>
Degree of protection (IP)	<b>IP20</b>		


## Technical data

Code	SLI035059WW_PW
Power	40 W
Nominal current	173 mA
Voltage	230 V
Energy consumption	40 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power supply included	+
Power factor	0.9
Useful luminous flux*	4600 lm (360°)
Luminous flux**	3600 lm (360°)
Lamp efficacy	115 lm/W
Colour temperature	3000 K
Colour of light	WW
Beam angle	120 °
RA	>80
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20/+40 °
Lifespan	26000 h
Housing material	Aluminum/Steel/Plastic
Degree of protection (IP)	IP20
Colour	White
Dimension (AxBxC)	295x1195x25 mm
For use	Inside
Assembly method	On the ceiling, Recessed
Application	INT
Made in	PRC



## Related documents



 Declaration of Conformity



 Photometric file

