



Power	<b>64 W</b>	Voltage	<b>230 V</b>
Luminous flux*	<b>8200 lm (360°)</b>	Colour temperature	<b>4000 K</b>
Light colour	<b>Neutral white</b>	Beam angle	<b>120 °</b>
UGR	<b>&lt;19</b>	Protection class	<b>IP20</b>




 Declaration of Conformity



 Photometric file

**Technical data:**

Product code	SLI035063NW_PW
Power	64 W
Nominal current	280 mA
Voltage	230 V
Energy consumption	64 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power supply included	+
Power factor	0.9
Useful luminous flux*	8200 lm (360°)
Luminous flux**	7500 lm (360°)
Light efficiency	128 lm/W
Colour temperature	4000 K
Light colour	Neutral white
Beam angle	120 °
UGR	<19
RA	>80
Uniformity of color SDCM max	5
Dimmable	OPC
Working temperature range	-20/+40 °
Lifespan	50000 h
Housing material	Aluminum/TWORZYWO SZTUCZNE
Protection class	IP20
Colour	White
Dimension (axbxc)	595x1195x37 mm
For use	Inside
Assembly method	Recessed
Application	INT
Made in	PRC



\*Applies to the LED source used. \*\*Luminaire luminous flux