

ALGINE BACKLIGHT

SLI035064CW_PW

LED panel ALGINE BACKLIGHT, with a power of 26 W, high light efficacy 165 lm/W. It is made of high-quality components, supported by a 5-year warranty. It shines with a cold light colour (6000K), which is suitable for rooms where we need to be most focused and concentrated, such as technical workstations. Suitable for both surface and recessed mounting. The product is certified by the National Institute of Hygiene, so it can be used in rooms with high hygienic requirements.



Power	26 W	Voltage	230 V
Luminous flux*	4300 lm (360°)	Colour temperature	6000 K
Colour of light	CW	Beam angle	120 °
Degree of protection (IP)	IP20		

Technical data

Code	SLI035064CW_PW
Power	26 W
Nominal current	115 mA
Voltage	230 V
Energy consumption	26 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power supply included	+
Power factor	0.9
Useful luminous flux*	4300 lm (360°)
Luminous flux**	3900 lm (360°)
Lamp efficacy	165 lm/W
Colour temperature	6000 K
Colour of light	CW
Beam angle	120 °
RA	>80
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20/+40 °
Lifespan	50000 h
Housing material	Aluminum/Plastic
Degree of protection (IP)	IP20
Colour	White
Dimension (AxBxC)	595x595x32 mm
For use	Inside
Assembly method	On the ceiling, Recessed
Application	INT
Made in	PRC

Related documents



 Declaration of Conformity



 Photometric file

