



Power **30 W**  
Luminous flux\* **4000 lm (360°)**  
Light colour **CW**  
Protection class **IP20**

Voltage **230 V**  
Colour temperature **6000 K**  
Beam angle **120 °**



 User manual



 Declaration of Conformity



 Photometric file

Technical data:

|                              |                           |
|------------------------------|---------------------------|
| Product code                 | SLI035069CW_PW            |
| Power                        | 30 W                      |
| Nominal current              | 135 mA                    |
| Voltage                      | 230 V                     |
| Energy consumption           | 30 kWh/1000h              |
| Frequency                    | 50HZ Hz                   |
| Protection class             | I                         |
| Power supply included        | +                         |
| Power factor                 | 0.9                       |
| Useful luminous flux*        | 4000 lm (360°)            |
| Luminous flux**              | 3600 lm (360°)            |
| Light efficiency             | 133 lm/W                  |
| Colour temperature           | 6000 K                    |
| Light colour                 | CW                        |
| Beam angle                   | 120 °                     |
| RA                           | >80                       |
| Uniformity of color SDCM max | 5                         |
| Dimmable                     | No                        |
| Working temperature range    | -20/+40 °                 |
| Lifespan                     | 50000 h                   |
| Housing material             | Aluminum/Plastic          |
| Protection class             | IP20                      |
| Colour                       | White                     |
| Dimension (axbxc)            | 295x1195x32 mm            |
| For use                      | Inside                    |
| Assembly method              | surface mounted, recessed |
| Application                  | INT                       |
| Made in                      | PRC                       |



\*Applies to the LED source used. \*\*Luminaire luminous flux