ALGINE BACKLIGHT

SLI035069NW_PW

LED panel ALGINE BACKLIGHT, with a power of 30 W, high light efficacy 133 lm/W. It is made of high-quality components, supported by a 5-year warranty. Lights up with neutral light - the most universal colour (4000K), which is suitable for the rooms we use on a daily basis, ensuring comfort during everyday activities. Suitable for both surface and recessed mounting. The product is certified by the National Institute of Hygiene, so it can be used in rooms with high hygienic requirements.

Power	30 W	Voltage	230 V
Luminous flux*	4000 lm (360˚)	Colour temperature	4000 K
Colour of light	Neutral white	Beam angle	120 ˚
Degree of protection (IP)	IP20		

Wojnarowscy Sp. z o.o.
40-432 Katowice, Gospodarcza 16, Poland
www.spectrumled.eu

Technical data

Code	SLI035069NW_PW
Power	30 W
Nominal current	135 mA
Voltage	230 V
Energy consumption	30 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power supply included	+
Power factor	0.9
Useful luminous flux*	4000 lm (360°)
Luminous flux	3600 lm (360°)
Lamp efficacy	133 lm/W
Colour temperature	4000 K
Colour of light	Neutral white
Beam angle	120 °
RA	80
Light source included	Yes
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20/+40 °
Warranty	5 years
Lifespan	50000 h
(On/Off)	25000
Housing material	aluminum
Degree of protection (IP)	IP20
Colour	White
Dimension (AxBxC)	295x1195x32 mm
For use	Inside
Assembly method	On the ceiling, Recessed
Certified by the National Institute of Hygiene	Yes
Made in	PRC

*applies to the LED source used

Logistics data

Bulk packaging	6 pcs.
Quantity per pallet	72 pcs.
Gross weight (1 pcs.)	1.4 kg

Related documents

User manual

Declaration of Conformity

Photometric file

Wojnarowscy Sp. z o.o.
40-432 Katowice, Gospodarcza 16, Poland
www.spectrumled.eu